



AIRC-01230V

Compressed Air Controller

Principle workings of the Air Controller

The AIRC-01230V is a motorised ball valve that is installed in the compressed air line after the air receiver. The AIRC-01230V opens and closes the air supply to the factory, based on customer specific work shifts.

A typical compressed air system has air loss through pipe work connections, leaking float type drains etc.,

The AIRC-01230V will open the ball valve at the beginning of a working shift and close the ball valve when the working shift is over. From that point on, all compressed air will remain in the air receiver until the next working shift, rather than being lost through leakages.

The clever and versatile programming feature allows for customer specific settings and is totally adaptable to the working hours of each individual factory.

The AIRC-01230V can be installed in all pipe line systems up to 1". Remote switching kits are available to operate the AIRC-01230V from a distance.



COMMERCIAL BENEFITS

- Microprocessor controlled (7 day program feature - multiple cycles possible each day).
- Language selection feature (English, German, Spanish, French and Dutch).
- Easy to program (intuitive).
- Each individual day can be programmed according to specific working day shift requirements.
- LCD displaying the program cycle and the current time.
- External push button controls (disassembly not necessary).
- Battery life indication in the display.
- Fully automatic - no maintenance.
- Small compact design.
- Private labelling options.

TECHNICAL ADVANTAGES

- FPM seals.
- Stainless steel ball, valve is nickel plated brass.
- Slow ball valve rotation 90 degrees in 30 seconds (designed to avoid water-hammer when opening or closing).
- Extended programming features relating to valve open and close cycles (100).

AIRC-01230V

Compressed Air Controller

PRODUCT DIMENSIONS



AIRC-01230V SPECIFICATIONS

Supply voltage	230VAC or 115VAC 50/60 Hz
Power consumption	7W during cycle rotation
Opening/Closing duration	30 sec. /90°
Max. ambient temperature	50°C
Max. medium temperature	100°C
Minimum pressure	0 bar
Maximum pressure	16 bar
Valve	1" connection
Valve	Brass/nickel plated
Manual override	Yes
Remote controllable	Yes
Environmental protection	IP54
Timer display	24 hours
Programmable options	16 cycles/day, 7 days/week




Built-in quartz controlled timer with LCD display



Remote control option.



Should there be an electrical power failure, then the ball valve can be manually opened or closed



Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use.

Flotech Compressor & Vacuum Parts Ltd
Unit 8, Kinsealy Business Park, County Dublin, Ireland.
Tel: +353 1 846 4303 ■ E-Mail: info@flotech.ie